

### Product Overview

Confidex Carrier is a special label with strong grip to plastic surfaces. It can be attached easily to various containers, and with its excellent performance, provide new visibility to asset tracking applications.

### Specifications

Dimensions – 2.95 x 0.55 x 0.01 inches (73 x 8 x .2 mm)

Communication Protocol – EPC Class 1 Gen 2 / ISO 18000-6C

Frequency Range – 860 MHz – 960 MHz (Global)

Integrated Circuit (IC) / Memory

- NXP G2XL – 240 bits

Materials – Durable Label Material

Environmental Durability

- Temperature - -31F – 194F (-35C – 90C)
- Impact Resistance – Good

Mounting / Attachment – Adhesive

Performance (*using Motorola MC9090G hand-held unit*)

- Read Range – 6 feet
- Orientation Sensitivity – linear; performs best at 90 degrees to hand-held linear antenna

Options

- Printing and encoding services available



Copyright 2010 RFID TagSource

*Note: Tag performance and durability will vary based on RFID hardware configuration and other environmental conditions. Customers should evaluate tags for application suitability before committing to large order quantities.*

---

For More information on these and our ever increasing selection of standards based passive RFID tags contact:

RFID TagSource  
Waterfront Technology Center  
200 Federal Street, Suite 300  
Camden, NJ 08103  
866-915-RFID (7343) ext. 3  
customerservice@rfidtagsource.com  
www.RFIDTagSource.com