

Product Overview

A waterproof durable tag integrated into flexible fabric, the Sontec laundry tag is an excellent choice for a variety of textile and industrial laundry tracking applications.

Specifications

Dimensions – 3.15x0.99x0.004 in (80x25x0.1 mm)

Communication Protocol – EPC Class 1 Gen 2 / ISO 18000-6C

Frequency Range – 860 - 960 MHz (Global)

Integrated Circuit (IC) / Memory

- G2XM – 512 bits

Materials – Fabric

Environmental Durability

- Operating Temperature: -22°F – 185°F (-30°C - 85°C)
- Application Temperature: -40°F – 266°F (-40°C – 80°C)

Mounting / Attachment – Sewn

Performance (*using Motorola MC9090G hand-held unit*)

- Read Range – 3 feet
- Orientation Sensitivity – linear; performs best at 90 degrees to hand-held linear antenna

Options

- Customizable Logo
- Custom encoding services available



Copyright 2010 RFID TagSource

Note: Tag performance and durability will vary based on RFID hardware configuration and other environmental conditions. Customers should evaluate tags for application suitability before committing to large order quantities.

For More information on these and our ever increasing selection of standards based passive RFID tags contact:

RFID TagSource
Waterfront Technology Center
200 Federal Street, Suite 300
Camden, NJ 08103
866-915-RFID (7343) ext. 3
customerservice@rfidtagsource.com
www.RFIDTagSource.com